

# SI 4000/7500 Series

## Very High Pressure Reciprocating Pumps



### FLUID - END COMPONENTS

**Cylinder Body** is machined from a solid forged block of stainless steel and ultrasonically tested to give the best performance under tough working conditions.

**Discharge Valve Assembly** is tapered guided and spring loaded for positive closing action and higher efficiency. Valve and valve seats are made of hardened stainless steel, precision machined and ground.

The fluid-end design provides an inline configuration of the suction valve assembly and plunger to allow virtually unrestricted fluid flow. It minimizes the feed pressure requirement.

**Plungers** are made from hardened stainless steel with a thick layer of hard chrome plating. They are precision machined, ground, lapped and polished.

**Special packing seal** is provided against plunger with no-wear sensitive lips.

**Safety Valve** is integrally mounted with fluid cylinder body. It is preset and sealed at the factory to prevent water pressure from exceeding the limit, thus protecting the pump and accessories.

**Flange Mounted Automatic Unloader** consists of spring loaded non-return valve and a by-pass control valve to adjust the pressure to the desired level. It is used along with a high pressure gun and foot operated valve when there is no need for sudden starting and stopping. When the line is shut-off instantaneously, the unloader bypasses the water back to the pump, at

practically water inlet pressure. It therefore unloads and makes the pump run on no load. If a gun is started the bypass is stopped and the pump is put back to original pressure.

### POWER - END COMPONENTS

**Gearcase** of rugged cast iron protects the gears and serves as oil reservoir for continuous lubrication. Cover section quickly removable for easy service.

**Pinion & main gear** are helical cut and machined from high-strength alloy steel, and rotate in either direction. Integral pinion shaft is also machined from high-strength alloy steel.

**Automotive type crankshaft** is of high strength ductile iron.

**Shaft bearings** feature tapered roller bearings.

**Crankshaft journal bearings** are automotive type, steel-backed inserts.

**Connecting links** are ductile iron with replaceable bronze wrist-pin bearings. Wrist pins are press fitted into the crossheads.

**Piston "pony" rods** are smoothly ground and highly - polished stainless steel, threaded and pinned axially to crosshead.

Continuous splash lubrication is provided during either direction of rotation.

### H. P. REQUIREMENT

Performance Table at 1440 RPM PINION SPEED

Pump Type	Capacity in LPM	HP															
		5	7.5	10	12.5	15	20	25	30	40	50	60	75	80	100		
SI 4014	15.0	126	189	253	323	386	505	630	757	1110	1262						
SI 4018	24.0		112	154	189	232	309	386	472	630	787						
SI 4022	36.0			98	126	154	203	260	309	420	525						
SI 4026	50.0				91	112	147	182	224	295	378						
SI 4028	58.0				77	91	126	161	189	253	323						
SI 4030	66.0						112	140	168	224	281						
SI 4032	76.0							119	147	196	246						
SI 4036	96.0							98	112	154	189						
SI 7514	16.0							352	562	765	880	1042	1056	1170	1285		
SI 7522	40.0										476	580	704	739	880		
SI 7526	53.0										358	422	513	562	704		
SI 7528	62.0										306	372	454	496	605		
SI 7530	72.0										265	322	394	430	528		
SI 7532	82.0										234	285	346	379	464		
SI 7536	104.0										183	224	273	298	352		



## WASP PUMPS (INDIA) LLP

Regd. Sales Office & Works:  
 Plot No. 113, Road No. 21, Wagle Industrial Estate, Thane 400604  
 GST: 27AAFFW0904N1ZX, Tel: +91 98210 21183,  
 Email: wasppumps@rediffmail.com Website : www.wasppumps.com

